IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR LETTERS PATENT

TITLE: COMMUNICATION CONTROL UNIT AND
                  COMMUNICATION CONTROL METHOD

INVENTOR: Tomokazu SUDA

William S. Frommer
Registration No. 25,506
Dennis M. Smid
Registration No. 34,930
FROMMER LAWRENCE & HAUG LLP
745 Fifth Avenue
New York, New York 10151
Tel. (212) 588-0800

COMMUNICATION CONTROL UNIT AND

COMMUNICATION CONTROL METHOD

BACKGROUND OF THE INVENTION

The present invention relates to a communication
control unit and a communication control method. More
particularly, the present invention relates to a
communication control unit mounted on an information-
processing apparatus communicating with other equipment
through a network and relates to a communication control
method adopted by the communication control unit.

Conventionally, in an information-processing
apparatus connected to a network such as a serial bus,
data is exchanged between the apparatus and other
equipment by way of the network at a transmission speed
adjusted to capabilities of the apparatus and the other
equipment.

An information-processing apparatus connected to a
serial bus as such includes an embedded special
communication control unit. Processing at physical and
data-link layers is carried out by hardware of the
information-processing apparatus. In general, the
communication control unit is embedded in the
information-processing apparatus as an LSI chip. On the

1

other hand, application processing is carried out by an upper-level microprocessor also mounted on the information-processing apparatus. The upper-level microprocessor is referred to hereafter as a host.

Processing from initialization of the serial bus to setting of a transmission speed is explained as an example conforming to IEEE-1394 specifications. FIG. 5 shows timing charts of processing, which is carried out after the conventional bus-reset according to the IEEE-1394 specifications.

In accordance with the IEEE-1394 specifications, a bus-reset occurs due to connection of an apparatus such as a digital video camera to an IEEE-1394 bus. A digital video camera is abbreviated hereafter to merely a DV. An apparatus connected to the IEEE-1394 bus is referred to hereafter as a node. When a bus reset occurs, each node automatically resets its topology, and transmits a self-ID packet. A self-ID packet of a node is a packet containing a self_ID uniquely assigned to the node. As shown in FIG. 5, a self_ID1 packet, a self_ID2 packet and a self_ID3 packet are sequentially transmitted through the IEEE-1394 bus serving as part of a physical layer employed in a node one packet after another from respectively an apparatus 1, an apparatus 2 and an

2

apparatus 3, which are not shown in the figure. At a LINK layer employed in the node, the self_ID1 packet, the self_ID2 packet and the self_ID3 packet, which are received from the physical layer, are sequentially processed one packet after another and then transferred to a host of the same node. The host in each node stores the processed self_IDs in a storage area in the host. A self_ID packet transmitted by a last node is followed by a sub-action gap (SG). Following the first sub-action gap, data can be exchanged between the node and another node.

In the above example, the last node is the apparatus 3. During a period between the transmission of the self_ID3 packet from the apparatus 3 and the sub-action gap, the host of the node 1 analyzes the self_IDs of other nodes, namely, the nodes 2 and 3. In addition to a number assigned to the node, a self_ID peculiar to a node includes SP information indicating a maximum transmission speed that the node is capable to keep up with. The host thus identifies a transmission speed of each node from the SP information of the node, and sets an optimum transmission speed. In a transmission of a packet, a transmission speed which has been set is supplied to a serial-bus controller for controlling the IEEE-1394 serial bus with a speed code. The packet is

3

thus transferred through the IEEE-1394 serial bus at a transmission speed determined by the speed code.

Since a host of a node analyzes transmission speeds of other nodes in accordance with the conventional technology as described above, however, there is raised a problem of an increased processing load to be borne by the host.

As described above, the host has a storage area for storing self_IDs of nodes and must analyzes the self_IDs during a period between the transmission of a self_ID from the last node and the issuance of a sub-action gap. For this reason, in the first place, in the case of a serial bus connectable to a number of apparatuses, the host employed in each of the apparatuses must preserve a storage area for storing the self_IDs of other apparatuses. In the second place, during a period of about 10 microseconds between the transmission of a self_ID from the last node and the issuance of a sub-action gap, the self_IDs must all be analyzed. Since the processing load borne by the host increases considerably, however, it will be difficult to bear such a processing load by using a less powerful host.

In addition, if the analysis of the self_IDs is not completed before the first sub-action gap, data must be

4

exchanged at a lowest transmission speed, causing the band to be wasted.

SUMMARY OF THE INVENTION

It is thus an object of the present invention addressing the problems described above to provide a communication control unit capable of reducing a processing load borne by a host to analyze transmission speeds of nodes.

In order to solve the problems described above, in accordance with an aspect of the present invention, there is provided a communication control unit mounted on an information-processing apparatus communicating with other apparatuses each serving as a node of a network through the network connecting the apparatuses with each other and used for controlling communications between the information-processing apparatus with the other apparatuses through the network. The communication control unit includes a transmission-speed storage means for storing a transmission speed at which data is to be communicated with other nodes connected to the network, a transmission-speed-information-acquiring means for acquiring transmission-speed information on a transmission speed set in another node connected to the

network for communicating data from the other node and a transmission-speed-setting means for setting a predetermined transmission speed in the transmission-speed storage means in advance, comparing the predetermined transmission speed set in the transmission-speed storage means in advance with the acquired transmission-speed information on a transmission speed set in another node connected to the network and carrying out transmission-speed-setting/updating processing to update a transmission speed stored in the transmission-speed storage means on the basis of a result of comparison.

In order to solve the problems described above, in accordance with another aspect of the present invention, there is provided a communication control method adopted by a communication control unit mounted on an information-processing apparatus communicating with other apparatuses each serving as a node of a network through the network connecting the apparatuses with each other and used for controlling communications between the information-processing apparatus with the other apparatuses through the network. The communication control method includes the steps of setting a transmission speed at which data is to be communicated

6

with other nodes connected to the network in advance,
acquiring transmission-speed information on a
transmission speed set in another node connected to the
network for communicating data from the other node,
comparing the predetermined transmission speed set in
advance with the acquired transmission-speed information
on a transmission speed set for communicating data in the
other node, selecting an optimum transmission speed in
accordance with a result of comparison and, if necessary,
setting the selected optimum transmission speed to update
the predetermined transmission speed set in advance and
repeatedly carrying out the processing starting with the
step of acquiring transmission-speed information on a
transmission speed if there is a further node, from which
transmission-speed information on a transmission speed
has not been acquired.

As described above, in a communication control unit
provided by the present invention, a predetermined
transmission speed is set in advance. The communication
control unit is employed in a data-processing apparatus
serving as a node connected to a network. The
communication control unit receives information on a
transmission speed from another node connected to the
network. Every time information on a transmission speed

7

of another node is received from the other node, the transmission speed is compared with the predetermined transmission speed to select either the transmission speed or the predetermined transmission speed stored in advance as an optimum transmission speed. If necessary, the selected optimum speed is used as a replacement of the predetermined transmission speed stored beforehand.

In an information-processing apparatus incorporating such a communication control unit, it is the control unit that selects an optimum transmission speed as described above. Thus, a storage area for storing information used for determining an optimum transmission speed is not required in the host. In addition, it is also no longer necessary for the host to analyze received transmission speeds in order to determine an optimum transmission speed during a short period of time between a transition of processing to the host and a start of communication. As a result, the processing load borne by the host can be reduced substantially. Moreover, since an optimum transmission speed can be determined during a predetermined period of time, data can be communicated at the optimum transmission speed right after the completion of the initialization of the bus. Thus, the transmission band

8

can be utilized with a high degree of efficiency.

Furthermore, a communication control method
provided by the present invention includes the steps of
setting a transmission speed at which data is to be
communicated with other nodes connected to the network in
advance, acquiring transmission-speed information on a
transmission speed set in another node connected to the
network for communicating data from the other node,
comparing the predetermined transmission speed set in
advance with the acquired transmission-speed information
on a transmission speed set for communicating data in the
other node and selecting an optimum transmission speed in
accordance with a result of comparison and, if necessary,
setting the selected optimum transmission speed to update
the predetermined transmission speed set in advance. If
there is a further node, from which transmission-speed
information on a transmission speed set for communicating
data in the further node has not been acquired, the steps
of the method are again executed for this further node,
starting with the step of acquiring transmission-speed
information on a transmission speed set for communicating
data in the further node. This processing is carried out
repeatedly for all other nodes connected to the network.

In an information-processing apparatus

9

incorporating such a communication control unit, it is the control unit that selects an optimum transmission speed as described above. Thus, a storage area for storing information used for determining an optimum transmission speed is not required in the host. In addition, it is also no longer necessary for the host to analyze received transmission speeds in order to determine an optimum transmission speed during a short period of time between a transition of processing to the host and a start of communication. As a result, the processing load borne by the host can be reduced substantially.

The above and other objects, features and advantages of the present invention will become apparent from the following description and the appended claims, taken in conjunction with the accompanying drawings in which like parts or elements denoted by like reference symbols.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram showing the configuration of a network connecting data transmission apparatuses each incorporating a communication control unit implemented by an embodiment of the present invention;

10

FIG. 2 is a diagram showing the configuration of an IEEE-1394 self_ID packet;

FIG. 3 is a flowchart representing the communication control method adopted by the communication control unit implemented by the embodiment of the present invention;

FIG. 4 shows timing charts of post-bus-reset operations carried out by the communication control unit provided by the present invention; and

FIG. 5 shows timing charts of processing, which is carried out after the conventional bus reset according to the IEEE-1394 specifications.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

A preferred embodiment of the present invention is explained by referring to diagrams. A network in the embodiment is an IEEE-1394 serial bus. FIG. 1 is a block diagram showing the configuration of a network connecting data transmission apparatuses each incorporating a communication control unit implemented by an embodiment of the present invention.

A data transmission apparatus 100 (or node 1) incorporating a communication control unit implemented by the embodiment of the present invention composes a

11

network in conjunction with other nodes 2 and 3, which are connected to node 1 by an IEEE-1394 serial bus 200 referred to hereafter simply as a bus. In the figure, nodes 2 and 3 are denoted by reference numerals 101 and 102 respectively. The internal configurations of nodes 2 and 3 are each identical with the data transmission apparatus 100 (node 1).

The data transmission apparatus 100 (node 1) is typically an information-processing apparatus such as a DV or a personal computer. Information such as data representing a moving picture is exchanged among the nodes through the bus 200. The data transmission apparatus 100 includes a physical layer 110, a communication control unit 120 and a host 130. The physical layer 110 carries out processing prescribed for a physical layer by the IEEE-1394 specifications. The communication control unit 120 carries out communication control processing including processing prescribed for a data-link layer by the IEEE-1394 specifications. The host 130 carries out application processing. The communication control unit 120 includes a LINK layer 121, a transmission speed-information-extracting means 122 for extracting transmission speed information abbreviated hereafter to an SP, a transmission speed-setting means

12

123, a transmission speed storage means 124 and a peripheral unit 125.

A data packet coming through the bus 200 is passed on to the communication control unit 120 employed in the data transmission apparatus 100 (node 1) by way of the physical layer 110, being received by the LINK layer 121 employed in the communication control unit 120. As described above, the physical layer 110 carries out signal processing prescribed for a physical layer by the IEEE-1394 specifications. On the other hand, the LINK layer 121 carries out signal processing prescribed for a data-link layer by the IEEE-1394 specifications. In accordance with the IEEE-1394 specifications, a bus-reset is generated by a node recognizing connection of a new apparatus to the bus 200, disconnection of an existing apparatus from the bus 200 or a similar change in the configuration of the bus 200. In the event of a bus-reset, each node automatically recognizes the topology, sets a node address or a node number and outputs a self_ID packet to the bus 200. A self_ID packet transmitted after a bus-reset by node 2 (or the data transmission apparatus 101) or node 3 (or the data transmission apparatus 102), both of which are connected to the bus 200, is supplied to the SP-extracting means 122 by way of the physical

13

layer 110 and the LINK layer 121.

The self_ID packet is explained as follows. FIG. 2 is a diagram showing the configuration of an IEEE-1394 self_ID packet.

A self_ID packet of a node contains node identification information for identifying each node. The self_ID packet includes a node number (phy_ID), the existence/nonexistence of a LINK layer (L), an inter-packet gap (gap_cnt) and transmission-speed information (SP). An SP used in the present invention is explained below. Explanation of the other information is omitted.

An SP of a node represents a maximum transmission speed that the node is capable of keeping up with. In accordance with the IEEE-1394 specifications, at present, a transmission speed can be set at 100 Mbps, 200 Mbps or 400 Mbps. The SP is 2 bits set at "00b", "01b" or "10b" to represent a transmission speed of 100 Mbps, 200 Mbps or 400 Mbps respectively. For example, a node having an SP of "00b" is capable of communicating only at a transmission speed of 100 Mbps. A node having an SP of "01b" is capable of communicating at a transmission speed of 200 Mbps or 100 Mbps. A node having an SP of "10b" is capable of communicating at a transmission speed of 400 Mbps, 200 Mbps or 100 Mbps.

14

Referring back to FIG. 1, the SP-extracting means
122 is a transmission-speed-information-acquiring means
for acquiring the transmission-speed information of
another node. To put it in detail, the SP-extracting
means 122 is a transmission-speed-information-extracting
means for extracting an SP from a self_ID packet which
includes node identification information received by a
node-identification-information-receiving means including
the physical layer 110 and the LINK layer 121. Each time
a self_ID packet coming through the bus 200 is passed on
to the communication control unit 120 by way of the
physical layer 110, being received by the LINK layer 121
employed in the communication control unit 120, the SP-
extracting means 122 extracts an SP described above from
the self_ID packet and supplies the extracted SP to the
transmission-speed-setting means 123.

The transmission-speed-setting means 123 sets a
predetermined transmission speed and stores the speed in
the transmission-speed-storing means 124 in advance. Each
time an SP is received from the SP-extracting means 122,
the transmission-speed-setting means 123 compares the SP
with the predetermined transmission speed stored in the
transmission-speed-storing means 124 in advance, selects
an optimum transmission speed and, if necessary, stores

15

the optimum transmission speed in the transmission-speed-storing means 124 to update the set transmission speed stored in the transmission-speed-storing means 124 in advance. An optimum transmission speed can be selected arbitrarily by adoption of a technique proper for the network. If the network is a serial bus, for example, a lowest transmission speed that a node connected to the serial bus is selected as an optimum transmission speed. To be more specific, the transmission-speed-setting means 123 compares the SP with the predetermined transmission speed stored in the transmission-speed-storing means 124 in advance and, if the transmission speed specified by the SP is found lower than the predetermined transmission speed stored in the transmission-speed-storing means 124 in advance, the transmission speed specified by the SP is selected and stored in the transmission-speed-storing means 124 to replace the set transmission speed stored in the transmission-speed-storing means 124.

The transmission-speed-storing means 124 is a storage area used for storing a transmission speed set by the transmission-speed-setting means 123. At the start of processing carried out by the transmission-speed-setting means 123, a predetermined transmission speed is set and stored in the transmission-speed-storing means 124 in

16

advance. Each time a self_ID packet is received from

another node, however, the transmission speed stored in

the transmission-speed-storing means 124 is replaced by a

selected optimum transmission speed provided that the

selected optimum transmission speed is lower than the

transmission speed stored in the transmission-speed-

storing means 124. After a self_ID packet is received

from a last node, a final transmission speed optimum for

the network should have been set in the transmission-

speed-storing means 124.

The peripheral unit 125 facilitates exchanges of

data between the host 130 and the communication control

unit 120 in general and between the host 130 and the LINK

layer 121 employed in the communication control unit 120

in particular.

The host 130 carries out application processing and

controls the data transmission apparatus 100 (node 1) as

a whole. The host 130 is capable of obtaining an optimum

transmission speed stored in the transmission-speed-

storing means 124 through the peripheral unit 125. In

addition, the host 130 issues a command to the LINK layer

121 by way of the peripheral unit 125.

The operation of the data transmission apparatus

100 (node 1) having such a configuration is explained as

follows. In the event of a bus-reset, the communication
control unit 120 employed in the data transmission
apparatus 100 (node 1) is informed of the bus-reset. At
that time, the transmission-speed-setting means 123 sets
and stores a predetermined transmission speed in the
transmission-speed-storing means 124. When a self_ID
packet is received from another node connected to the bus
200, the self_ID packet is supplied to the SP-extracting
means 122 by way of the physical layer 110 and the LINK
layer 121. An example of the other node is the data
transmission apparatus 101 (node 2) or the data
transmission apparatus 102 (node 3). The SP-extracting
means 122 extracts an SP from the received self_ID packet
and supplies the SP to the transmission-speed-setting
means 123. The transmission-speed-setting means 123
compares the SP with the predetermined transmission speed
stored in the transmission-speed-storing means 124 and
selects an optimum transmission speed. If necessary, the
transmission-speed-setting means 123 stores the selected
optimum transmission speed in the transmission-speed-
storing means 124 to replace the predetermined
transmission speed stored in the transmission-speed-
storing means 124 in advance. Assume that an optimum
method for selecting a lowest transmission speed is

18

adopted. In this case, if the transmission speed specified by the SP is found lower than the predetermined transmission speed stored in the transmission-speed-storing means 124 in advance, the transmission speed specified by the SP is selected and stored in the transmission-speed-storing means 124 to replace the set transmission speed stored in the transmission-speed-storing means 124 in advance. Each time a self_ID packet is received from another node, the SP-extracting means 122 extracts an SP from the self_ID packet whereas the transmission-speed-setting means 123 analyzes the SP and, if necessary, updates the transmission speed stored in the transmission-speed-storing means 124. This processing is carried out for each received self_ID packet. When the last self_ID packet is received and the transmission-speed-setting means 123 determines a transmission speed based on the SP extracted from the packet, a transmission speed optimum for the network 200 is stored in the transmission-speed-storing means 124. Thereafter, a packet is transmitted at the optimum transmission speed stored in the transmission-speed-storing means 124.

As described above, since it is the communication control unit 120 that carries out the processing to analyze transmission-speed information received from each

19

node and set a transmission speed optimum for the bus 200

as a result of the analyses, the processing load borne by

the host 130 can be reduced considerably. In addition,

since the processing to set a transmission speed is

carried out every time a self_ID packet is received from

another node, the processing can be completed before a

sub-action gap. Thus, packets can be transmitted at a

transmission speed optimum for the bus 200 from the

beginning.

Next, a communication control method adopted by the

communication control unit provided by the present

invention is explained. FIG. 3 is a flowchart

representing the communication control method adopted by

the communication control unit implemented by the

embodiment of the present invention. The communication

control method is used for selecting a highest

transmission speed allowed for the node including the

communication control unit. Without adoption of this

communication control method, the node would otherwise

communicate data at a transmission speed lowest among a

transmission speed of 100 Mbps, a transmission speed of

200 Mbps and a transmission speed of 400 Mbps, which are

referred to hereafter as s100, s200 and s400 transmission

speeds respectively.

20

In the event of a bus-reset, the communication control unit 120 starts processing at the first step S10 of the flowchart shown in FIG. 3. First of all, at the next step S11, the predetermined s400 transmission speed is set in a register called max_speed. The max_speed register serves as the transmission-speed-storing means 124. Then, at the next step S12, a self_ID packet is received from another node. Subsequently, at the next step S13, an SP is extracted from the self_ID packet. Then, at the next step S14, the SP is compared with the s400 transmission speed stored in the max_speed register. If the s400 transmission speed stored in the max_speed register is found equal to or lower than the SP, the flow of the communication control method goes on to a step S15 at which the s400 transmission speed is sustained in the max_speed register as it is. If the SP is found lower than the s400 transmission speed stored in the max_speed register, on the other hand, the flow of the communication control method goes on to a step S16 at which the s400 transmission speed stored in the max_speed register is replaced by the SP.

To put it concretely, if the transmission speed stored in the max_speed register and the SP are both s400, the s400 transmission speed stored in the max_speed

21

register is sustained as it is. If the transmission speed stored in the max_speed register is s400 but the SP is s200 or s100, on the other hand, the s400 transmission speed stored in the max_speed register is replaced by the SP. If the transmission speed stored in the max_speed register is s200 but the SP is s400 or s200, the s200 transmission speed stored in the max_speed register is sustained as it is. If the transmission speed stored in the max_speed register is s200 but the SP is s100, on the other hand, the s200 transmission speed stored in the max_speed register is replaced by the SP. If the transmission speed stored in the max_speed register is s100, the s100 transmission speed stored in the max_speed register is never updated.

Then, at the next step S17, the self_ID packet is examined to form a judgment as to whether or not the packet has been received from a last node. If the self_ID packet is not a packet received from the last node, the flow of the communication control method goes back to the step S12 to receive another self_ID packet. If the self_ID packet is a packet received from the last node, on the other hand, the flow of the communication control method goes on to a step S18 at which the transmission speed stored in the max_speed register is adopted as the

22

optimum transmission speed. Then, at the next step S19,

the processing is ended. An operation to update the

optimum transmission speed stored in the max_speed

register is inhibited till the next initialization of the

bus 200.

As described above, since it is the communication

control unit 120 that carries out the processing to

analyze transmission-speed information received from each

node and set a transmission speed optimum for the bus 200

as a result of the analyses, the processing load borne by

the host 130 can be reduced considerably. In addition,

since the storage area for analyzing an SP and

determining a final optimum transmission speed is

implemented by the max_speed register for storing a

tentative optimum transmission speed, a large storage

area is not required for analyzing an SP and determining

a final optimum transmission speed in the communication

control unit 120. It is needless to say that such a large

storage area is not required either in the host 130.

The next description explains operations, from the

bus initialization to the processing to set an optimum

transmission speed, which are carried out by a data

transmission apparatus incorporating the communication

control unit provided by the present invention. FIG. 4

23

shows timing charts of post-bus-reset operations carried

out by the communication control unit provided by the

present invention.

In the event of a bus-reset, each node

automatically recognizes a topology and transmits a

self_ID packet. As shown in FIG. 4, a self_ID1 packet, a

self_ID2 packet and a self_ID3 packet are sequentially

transmitted one packet after another from respectively an

apparatus 1, an apparatus 2 and an apparatus 3, which are

not shown in the figure. The LINK layer 121 employed in

the communication control unit 120 sequentially receives

the self_ID1 packet, the self_ID2 packet and the self_ID3

packet from the physical layer 110, supplying the packets

to the transmission-speed-information-extracting means

122 employed in the communication control unit 120 one

packet after another. Every time a self_ID packet is

received, an SP is extracted from the packet. The SP is

analyzed and, if necessary, the SP is used for replacing

a tentative optimum transmission speed stored beforehand.

After the self_ID3 packet, which is the last received

self_ID packet, is analyzed for use as a possible

replacement of a tentative optimum transmission speed

stored beforehand, a final transmission speed optimum for

transmission of data among nodes, namely, the apparatuses

24

1, 2 and 3 connected to the bus 200 is determined.

Since the communication control unit 120 analyzes an SP every time a self_ID packet is received as described above, determination of a final optimum transmission speed can be completed before a sub-action gap (SG). As a result, data can be transmitted at an optimum transmission speed from the beginning starting with the first transmitted packet without the need for the host 130 to bear a processing load to determine a final transmission speed. In addition, since data can be exchanged at the optimum transmission speed right after the initialization of the bus, the transmission band can be utilized with a high degree of efficiency.

As described above, the network is a serial bus conforming to the IEEE-1394 specifications. However, the scope or the present invention is not limited to such a bus.

It should be noted that the processing functions described above can be executed by a computer. In this case, processing details of all the functions of the communication control unit are prescribed in advance by programs stored in a storage medium readable by the computer. The computer then executes the programs to carry out the functions. Examples of the storage medium

25

readable by the computer are a magnetic recording device and a semiconductor memory. A program sold in the market is normally stored in a portable recording medium such as a CD-ROM (Compact-Disk Read-Only Memory) or a floppy disk. Such a program can also be downloaded into a storage unit employed in the computer by way of a network to which the computer is connected. The program can also be transferred from the computer to another computer by way of the network. When the computer executes a program, the program is loaded from the storage unit such as a hard disk to a main memory of the computer.

While a preferred embodiment of the present invention has been described using specific terms, such description is for illustrative purposes only, and it is to be understood that changes and variations may be made without departing from the spirit or scope of the following claims.